

Svederusgatan 1-3, SE-754 50 Uppsala, Sweden. Tel: +46 18-15 61 90. Fax: +46 18-69 66 27.

email: info@trion.se. www.trion.se



AGS 560 ART. NO: 3653 | GRAFFITI REMOVER

AGS 560 is a mild graffiti remover. For outside and indoor use. Preferable for hard non-porous surfaces: especially plexiglas and other painted surfaces. Biodegradable.

Material

AGS 560 is especially developed for removal of graffiti on plexiglass. Effectively removes marker felt-tip pen and rust protective coating without attacking the plexiglass.

AGS 560 is also effective on other painted and delicate surfaces. **AGS 560** even works on spray paint graffiti, but the dissolving time is a little bit longer. Testing on a small surface prior to removal is recommended.

Graffiti removal

Use AGS 560 on a clean cloth or absorbent paper and wipe off graffiti. Turn the cloth so that the clean part is always used. Avoid smears of dissolved graffiti and wipe off residues of AGS 560. Rinse with water and dry with a clean cloth.

The dissolving process is easily interrupted with water.

Dosage

Use as concentrate.

Consumption

0,2 - 0,5 litre/m².

Technical data

- Yellowish-brown liquid.
- Supplied in 5 litres plastic container or 1 litre plastic bottle.
- Specific weight 0,92 kg/litre.
- Flash point >61°C.
- Mild odour.
- Contains 2-(2-butoxyethoxy) ethanol, 1-methoxy-2-propanol, 2-(2-Ethoxyethoxy) ethanol.

Storage

Store frost-free in closed original container.

Shelf life

Approximately 24 months in unopened container.

Precautions

Safety gloves, safety glasses in case of splashes.

Marking: Warning



Causes serious eye irritation.

Not classified as dangerous goods in ADR or IMDG.